

CE-8200



Features:

- 9999 Counts
- Auto power Off (APO)
- Conductor Size: 32mm x 65mm
- Max/Min, Data Hold
- Low battery indication
- Double Insulation Protection Level
- Spare 5.1 Test Ring, to detect Self Precision

RESISTANCE

Range	Resolution	Accuracy
0.010 - 0.099Ω	0.001Ω	± 1% of rdg + 0.01Ω digits
0.10 - 0.99Ω	0.01Ω	
1.0-49.9Ω	0.1Ω	± 1.5% of rdg + 0.5Ω digits
50.0-99.5Ω	0.5Ω	
100-199Ω	1Ω	± 2% of rdg + 1Ω digits
200-395Ω	5Ω	± 5% of rdg + 5Ω digits
400-590Ω	10Ω	± 10% of rdg + 10Ω digits
600-1000Ω	20Ω	± 20% of rdg + 20Ω digits

POWER

AA 1.5V X 4

- Standard Accessories : Hard Carrying Case, Test Lead, Manual
- Dimension : 285(H) x 85(W) x 66(D)mm

CE-8201



Features:

- 9999 Counts
- Auto power Off (APO)
- Conductor Size: 45mm X 32mm
- Max/Min, Data Hold
- Low battery indication
- Double Insulation Protection Level
- Spare 5.1 Test Ring, to detect Self Precision

CURRENT

Range	Resolution	Accuracy
100mA	0.1mA	± 2.5% of rdg + 1mA digits
300mA	0.3mA	± 2.5% of rdg + 2mA digits
1A	0.001A	± 2.5% of rdg + 0.003A digits
3A	0.003A	± 2.5% of rdg + 0.1A digits
10A	0.01A	± 2.5% of rdg + 0.03A digits
20A	0.03A	± 2.5% of rdg + 0.05A digits
30A		± 2.5% of rdg + 0.5A digits
40A		± 10% of rdg + 0.5A digits

RESISTANCE

Range	Resolution	Accuracy
0.01 Ω -	0.001Ω	±1.5% of rdg + 0.01Ω digits
1Ω - 9.99Ω	0.01Ω	±1.5% of rdg + 0.1Ω digits
10Ω - 99.9Ω	0.1Ω	±2.0% of rdg + 0.3Ω digits
100Ω -	1Ω	±3.0% of rdg + 1Ω digits
200Ω - 400Ω	5Ω	±6.0% of rdg + 5Ω digits
400Ω - 500Ω	10Ω	±10% of rdg + 10Ω digits
500Ω - 1200Ω	20Ω	20%

POWER

9V (6F22) X 1

- Standard Accessories : Hard Carrying Case, Test Lead, Manual
- Dimension : 285(H) x 85(W) x 66(D)mm

