

**DT-1**



- Measuring range: -50°C +300°C (-58°F 626°F)
- Accuracy :  $\pm 0.5\% \pm 1^\circ\text{C}(1.8^\circ\text{F})$
- Resolution : 0.1°C/0.1°F
- Probe Length : 145MM
- °C and °F selection
- Auto Power Off (APO)
- Water - Resistant
- Water Proof Level IP-54 (Only for DT-1)
- Power : 3 V "CR 1225" Button Cell (DT-1)
- Power : 1.5 V "AG 13" (DT-2)

**DT-2**



**DT-302-1/DT-302-2**



**Features:**

- Large LCD display makes reading clear
- Data Hold Function
- High Resolution 0.1°C/°F (DT-302-1)
- High Stability, high accuracy  
0.2% (DT-302-1)  
0.5% (DT-302-2)

**Technical Data :**

Basic Functions	Range	Accuracy	
		DT-302-1	DT-302-2
Temperature Range	-50°C - 199.9°C	$\pm 0.2\%$ of rdg + 1 digits	$\pm 0.3\%$ of rdg + 1 digits
	-50°C - 1000°C	$\pm 0.3\%$ of rdg + 1 digits	
	1000°C - 1300°C	$\pm 0.5\%$ of rdg + 1 digits	$\pm 0.5\%$ of rdg + 1 digits
	-50°F - 199.9°F	$\pm 0.3\%$ of rdg + 2 digits	
	-50°F - 1999°F	$\pm 0.5\%$ of rdg + 2 digits	$\pm 0.3\%$ of rdg + 2 digits
	T1-T2	-	$\pm 0.3\%$ (T1-T2) of rdg + 2 digits

Standard Accessories : Manual, TP01 Temperature Probe  
Dimension : 130(H) x 95(W) x 28(D)mm

