

HT-306



Features:

- Large Dual Display & Backlight
- Sampling Rate 2.5 sample per second
- Dual Display Temperature & Humidity
- Type K Temperature

Technical Data :

Function	Range & Resolution	Accuracy
Humidity	5.0 to 98.0% RH	± 3.5% RH
Temperature (K-type)	-20.0 to 199.9°C	± 3.0% of rdg + 4°C digits
	-20 to 1000°C	
	-4.0 to 199.9°F	± 3.0% of rdg + 7°F digits
-4 to 1832°F		

POWER

9V(6F22) X 1

- Standard Accessories : Carrying case, Manual, TP-01 Temperature Probe
- Dimension : 225(H) x 45(W) x 34(D)mm

HD-304



Features:

- Ambient temperature, Dew point temperature & Wet bulb temperature Fast Response Time
- Large-screen LCD and backlight
- Auto Power OFF (APO)
- 99 groups Data Logging.

Technical Data :

Basic Functions	Range	Resolution	Accuracy
Ambient Temperature	-20 to 60°C (-4 to 140°F)	0.1 °C / °F	±0.5°C (0 to 45°C) ±1.0°C(-20 to 0°C, 45 to 60°C)
RH	0 to 100%RH	0.1%	±2.0% RH(10% to 90%) ±3.0% RH(0% to 10%,90% to 100%)
WB (Wet bulb Temperature)	-20 to 60°C (-4 to 140°F)	0.1 °C / °F	±0.5°C (0 to 45°C) ±1.0°C(-20 to 0°C, 45 to 60°C)
DP (Dew point Temperature)	-50 to 60°C (-58 to 140°F)	0.1 °C / °F	±0.5°C (0 to 45°C) ±1.0°C(-50 to 0°C, 45 to 60°C)

POWER

AA 1.5V X 4

- Standard Accessories : Hard Carrying Case, Manual
- Dimension : 184 (H) x 60 (W) x 29 (D) MM

