

DT-2229

Features:

- Digit 10mm LCD Display
- Ranges: H,M,L
(High, Medium, Low)
- Flash Adjust:
Coarse adjustment,
Fine adjustment
X2 and $\div 2$ for fast Check
- Triggering Mode: Interior/Exterior



Technical Data :

Basic Function	Range	Resolution	Accuracy
Flashes Per Minute (FPM)	50 - 20,000 FPM	0.1 FPM (50 - 999.9FPM) 1FPM (Over 1000 FPM)	$\pm 0.05\%$ of rdg + 1 digits

Special Function :

Sampling Time	0.3 Second	Power	AC 220V
Flash Tube Lifetime	Million Times		

- Standard Accessories : Manual, Spare Flash Tube
- Dimension : 220(H) x 125(W)x125(D)mm

EASY LOG



Features:

- Memory for 32,700 readings
- LCD to show logging information easily
- Free selectable measurement cycle from 1sec to 24hrs.
- Battery life: more than 3 years (Under Ideal condition at 22°C)
- Display all status for Alarm and Record through 2 LED's.
- Alarm display if user-defined max/min values are exceeded
- Analysis software used to view graphically or Text mode For logging data.
- USB Computer Interface
(Advanced Software Program for all windows)

Technical Data :

Basic Functions	RH		Temp.			
Measuring Range	0 ~ 100%RH		-40°C ~ 70°C		-40°F ~ 158°F	
Accuracy	0 ~ 35% & 80 ~ 100% RH	+5% RH	-40°C ~ 40°C	±1.0 °C	-40°F ~ 104°F	±1.8 °F
	35% ~ 80% RH	+3% RH	40°C ~ 70°C	±2.0 °C	104°F ~ 158°F	±3.6 °F
Resolution	0.1%RH		0.1°C			
Memory	32,000 (16,000each for temperature and Humidity)					
Measuring Rate	1sec. to 24hrs					
Response Time	< 30 S					

Special Function :

Memory	32700 readings	Power	3.6V ER 14250 X 1
--------	----------------	-------	-------------------

- Standard Accessories : Holding Case, Safety Lock USB Cable with Software
- Dimensions : 94.8(H) x 51.4(W) x 29.5(D)mm

