

MTX-2



Features:

- °C or °F Selection
- Laser Target Pointer Selection
- Automatic Data Hold Function
- Auto Power Off (APO)
- Adjustable Emissivity

Technical Data :

Range	Resolution	Accuracy
-50°C to 550°C (-58°F to 1022°F)	0.1°C (0.1)°F	-50°C ~ 0°C / -58°F ~ 32°F: $\pm 4^\circ\text{C}/7.2^\circ\text{F}$ 0°C ~ 550°C / 32°F ~ 1022°F: $\pm 2\%$ ($\pm 2^\circ\text{C}/3.6^\circ\text{F}$)
Distance Spot Ratio		13:1
POWER		
9V (6F22) X 1		
Standard Accessories	Soft carrying case, Manual	
Dimension	155 x 99 x 28mm	

MT4/MT6



Features:

- °C or °F Selection
- Laser Target Pointer Selection
- Data Hold Function
- Auto Power OFF (APO)
- Backlight

Technical Data :

Basic Functions	MT4	MT6
Temperature Range	-30°C~550°C(-4°F~986°F)	-30°C~750°C(-4°F~1382°F)
Accuracy	± 2.0% OF rdg+2°C digits	± 2.0% of rdg+2°C digits
Distance Spot Ratio	12:1	
Emissivity	adjustable from 0.1-1.0	
Response Time & Wavelength	Less Than 500ms & (8~14)um	
Repeatability	±1% or ± 1°C	
Resolution	0.1°C or 0.1°F	
POWER		
9V (6F22) X 1		
• Standard Accessories : Soft carrying case, Manual		
• Dimensions : 132(H) x 55(W) x 168(D) mm		